



CENOVNIK LED I LCD DISPLEJA I VIDEO ZIDOVA

NEODOLJIVI OSEĆAJ SIGURNOSTI

Sadržaj

Reklamni, info displeji.....	3
Interaktivni ekrani.....	4
Video zidovi za unutra.....	5
Kontroleri i dodatna oprema.....	6

HIKVISION



DS-D6032FN-B

Digitalna Full HD signalizacija.

Veličina ekrana 32 inča. Rezolucija 1920x1080. Brightness 350 cd/m². Contrast ratio 4000:1. Refresh Rate 60Hz. Operativni sistem Android. 1x Audio in, 2x HDMI, 1 x VGA, 1x audio out. 2x zvučnika. Mrežni interfejs Lan i WiFi. 2x USB 2.0, 1 x TF Card, 1x BT 4.0. Radna temperatura 0 do 40 C.

HIKVISION



DS-D6043UN-B

Digitalna 4K signalizacija.

Veličina ekrana 43 inča. Rezolucija 3840x2160. Brightness 500 cd/m². Contrast ratio 4000:1. Refresh Rate 60Hz. Operativni sistem Android. 1x Audio in, 2x HDMI, 1 x VGA, 1x audio out. 2x zvučnika. Mrežni interfejs Lan i WiFi. 2x USB 2.0, 1 x TF Card, 1x BT 4.0. Radna temperatura 0 do 40 C.

HIKVISION



DS-D6055UL-B/S

Info/marketing LCD displej.

Veličina ekrana 54.5 inča. Rezolucija 1920x1080. Brightness 500 cd/m². Kontrast 3500. 1 Lan, WiFi. USB2.0 x2. 2 zvučnika. Memorija 8GB, podržava TF do 32GB. Podržava sledeće formate: DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, TS, FLV, WEBM, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF, MXMF, RTTTL, RTX, OTA, IMY, JPG, JPEG, BMP, GIF, PNG. Radna temperatura 0 - 40C. Potrošnja <150W.

dhua
TECHNOLOGY



LDV55-SAI200

Info/marketing LCD displej.

Veličina ekrana 55 inča. Aspect ratio 9:16. Rezolucija 1920x1080. 16.7M boja. Kontrast 1200:1. RJ45, USB2.0 x2, SD x1, RS232, WiFi, 2 zvučnika po 2w. Memorija 8GB. Radna temperatura -10 - +55. Potreban nosač/postolje za postavku na tlo: LDV55-DZ. Podržava slike, audio, video, PDF, prenos slike video nadzora, vremensku prognozu, itd. Ugrađeni softver za multimediju i USB plejer pružaju više metode za reprodukciju sadržaja na ekranu.

dhua
TECHNOLOGY



LDV55-DZ

Postolje za LDV55-SAI200.

HIKVISION



DS-D4215MI-070H(B)

LED Panel.

Integriran kontroler. Rezolucija 384x1080/60Hz. Ugao gledanja 160 stepeni. Preporučena daljina gledanja 2m. Radna temperatura -10 - 40 stepeni. Dimenzije 613mmx1695mm.5x68.1mm



HIKVISION



DS-D5ABKY2-S

Mobilni stojeći nosač za interaktivne ekrane od 55 do 75 inča.

SPCC visokokvalitetna čelična ploča, sive boje.
Dimenzije: 1.160mm x 688mm x 1.560mm.
Težina 20kg. Nosivost do 85kg.

HIKVISION



DS-D5B75RB/C

Interaktivni 4K touch screen ekran.

Veličina ekrana 75 inča. Rezolucija 3840x2160. Brightness 350 cd/m². Contrast ratio 1200:1. Refresh Rate 60Hz. Pixel pitch 0.143(H) x 0.430 (V)mm. Operativni sistem Android. 2x HDMI IN (max 4K @ 60Hz), 1 x HDMI out. 2 zvučnika 16W. 2 Mrežna interfejsa i Bluetooth 5.0. 2x USB 2.0. Radna temperatura 0 do 40 C. Potrošnja 300W.

HIKVISION




DS-D5C86RB/B

Interaktivni 4K touch screen ekran.

Veličina ekrana 86 inča. Rezolucija 3840x2160. Brightness 400 cd/m². Contrast ratio 5000:1. Refresh Rate 60Hz. Pixel pitch 0.1645(H) x 0.4935 (V)mm. Posедује kameru 48MP za slike i 8mp za video. Operativni sistem Android. 3x HDMI IN (max 4K @ 60Hz), 1 x HDMI out. 2 Mrežna interfejsa. 4x USB 3.0, 1x USB 2.0. Radna temperatura 0 do 40 C. Potrošnja 300W.

HIKVISION



DS-D4218FI-CWFH

LED displej za video wall.

Dimenzije: 600 (W) × 337.5 (H) × 61 (D) mm.
Gustina pixela: 284444 dots/m²
Rezolucija: 320x180.
Površina: 0,2025m².
Težina: 8,3kg.

HIKVISION



DS-D4225FI-CWFH

LED displej za video wall.

Unutrašnja montaža.
Rezolucija ekrana: 240x136.
Površina: 0,2025m².
Dimenzije: 600 mm × 337.5 mm × 50.9 mm.
Težina: 5,4kg.
Gustina pixela: 161185 dots/m².
Nivo zaštite: Prednja strana IP60.
Radna temperatura: -20°C ~ +60°C.

HIKVISION



DS-D2055LE-G

LCD ekran.

Ekran 55-inča. Širina okvira 1.8mm. Rezolucija 1920x1080. Brightness 500 cd/m². Kontrast 1400:1. Odziv 8ms. 1x HDMI in, 1x DVI, 1x VGA, 1x USB. 1x HDMI OUT, 1x DP OUT. Radna temperatura 0 do 40°C. Dimenzije 1211.54mm x 682.34mm x 68.9mm. Potrošnja 192W.

HIKVISION



DS-DN5501W

Zidni nosač za 55 inča ekrane.

Crne boje. Materijal: hladno valjana čelična ploča. Dimenzije 736mm x 684.5mm x 65mm. Težina 12.6kg.

HIKVISION



DS-DL226033W

LED modularni zidni nosač.

Nosač crne boje. Dimenzija 1240mm x 710mm x 80mm. Težina 4.9KG.

HIKVISION



DS-D60C-B

Distributivni uredjaj za led ekrane.

Centralizovano upravljanje. Daljinska kontrola i upravljanje jednim ili vise ekrana.

Podržava slike,audio,video,PDF,streaming media, web stranice, uzivo video... Fleksibilni programski raspored. Operativni sistem Android 6.0.1. 8GB memorije. Podržava TF Card 32GB. 1x audio in, 1x audio out. 1x hdmi. 1x LAN 100m, Wifi. 2x USB 2.0, Bluetooth 4.0. Radna temperatura 0 do 50C. Napajanje 12VAC, 2A.

HIKVISION



DS-D42C08-H

LED kontroler

Video i audio ulazi: 2x HDMI, 1x DP, 1x DVI.

Video i audio izlaz: 1x HDMI.

Mrežni interfejs: 8.

Kontrolni interfejs: RJ45x1.

DPI.2 ulaz: Do 4096x2160@60Hz.

Dualni HDMI2.0 ulaz: 4096x2160@60Hz (Podržano do 7680x1080@60Hz).